



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 041 848 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:

04.10.2000 Bulletin 2000/40

(51) Int Cl.7: **H04Q 7/38**

(21) Application number: 99107648.0

(22) Date of filing: 16.04.1999

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(72) Inventors:

- Weber, Matthias  
81927 München (DE)
- Winkler, Gregor  
c/o Sony International (Europe) GmbH  
85609 Aschheim (DE)

(30) Priority: 12.03.1999 WOPCT/EP99/01646

(71) Applicant: Sony International (Europe) GmbH  
50829 Köln (DE)

(74) Representative: Körber, Martin, Dipl.-Phys. et al  
Mitscherlich & Partner  
Patentanwälte  
Sonnenstrasse 33  
80331 München (DE)

(54) **Protecting a predetermined area from disturbing usage of mobile terminals by means of a paging message**

(57) The present invention relates to a base station (1, 1') and a method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless telecommunication system. Further, the present invention relates to a mobile terminal (7) the operation mode of which can be changed by mode change information received from a base station (1, 1') to protect a predetermined area. A predetermined area might be an area, in which at least a high frequency part of the mobile terminals should be switched off automatically to avoid interference with electronic or electric devices, e. g. in hospital or airplanes. In other areas, e. g. restaurants, operas or the like, it is sufficient to reduce the volume of

acoustic signals to be output so that other people in the area are not disturbed. The base station (1, 1') for protecting the predetermined area according to the present invention thereby comprises generating means (2, 2') for generating mode change information for changing an operation mode of the mobile terminals to protect the predetermined area, and transmitting means (3, 3') for transmitting the generated mode change information within the predetermined area by means of a paging message of a paging channel of the wireless telecommunication system. The use of the paging message thereby provides a simple and effective way to transmit the mode change information according to the present invention.




Fig. 2

EP 1 041 848 A1

## Description

[0001] The present invention relates to a base station for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system, to a method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system and to a mobile terminal for a wireless cellular telecommunication system.

[0002] In many areas the use of mobile terminals of wireless telecommunication systems is regarded as a nuisance for other people, like in restaurants or in the opera, or even dangerous in places like hospitals or airplanes. In the first case particularly audible signals output from mobile terminals are disturbing other people or the spectacle being given. In the second case, the use of mobile terminals, particularly the transmission of high frequency electromagnetic waves, can disturb other electronic devices or the like by interfering with their circuitry what can lead to severe incidents. It is therefore very important to provide a way to protect predetermined areas from disturbing usage of mobile terminals within these areas. Particularly, the protection of a predetermined area should not depend on the user's will, e. g. on a user's input of information to the mobile terminal.

[0003] EP 0 891 110 A1 discloses a method and a system for preventing a mobile terminal from causing disturbance within a predetermined area, e. g. inside a plane or inside of hospitals. Particularly, the disclosed method comprises the steps of transmitting a deactivation signal from a base station to a mobile terminal and deactivating a use of the output of the mobile terminal in response to the deactivation signal. Thereby, the transmission output is deactivated. The base station can either be an ordinary base station or a base station specifically designed for mainly transmitting the deactivation signal. Although EP 0 891 110 A1 describes, that the base station could be an ordinary base station, it is not disclosed how the deactivation signals could be implemented and transmitted in an ordinary telecommunication system.

[0004] The object of the present invention is therefore to provide a base station and a method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system, which protects a predetermined area by transmitting mode change information for changing an operation mode of the mobile terminals in a simple and effective way, whereby the mode change information is transmitted on the basis of a wireless cellular telecommunication system. The object of the present invention is further to provide a mobile terminal for a wireless cellular telecommunication system, which can be controlled by such mode change information so that the predetermined area is protected from disturbing use of the mobile terminal.

[0005] The above object is achieved by a base station for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system, with generating means for generating mode change information for changing an operation mode of the mobile terminals to protect the predetermined area, and transmitting means for transmitting said generated mode change information within said predetermined area by means of a paging message of a paging channel of a wireless telecommunication system.

[0006] The above object is further achieved by a method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system, with the steps of generating mode change information for changing an operation mode of the mobile terminals to protect the predetermined area, and transmitting said generated mode change information within said predetermined area by means of a paging message of a paging channel of a wireless telecommunication system. According to the present invention, the paging message from the base station comprises, consists of or relates to mode change information for changing an operation mode of the mobile terminal.

[0007] Thus, the base station and the method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system enable a simple and effective way to change the operation mode of mobile terminals within the predetermined area automatically so that the predetermined area is protected.

[0008] The base station of the present invention can thereby be an ordinary base station of the wireless cellular telecommunication system which additionally to its usual elements comprises the generating means and the transmitting means according to the present invention whereby the transmitting means also transmits normal signalling messages or user data information of the telecommunication system. Alternatively, the base station of the present invention is a specialised base station with a restricted functionality compared to an ordinary base station. Depending on the required application, the specialised base station could comprise essentially the generating means and the transmitting means according to the present invention without further elements for communicating data in the telecommunication system. This last possibility would present a very simple and cost-effective way to protect certain areas according to the present invention.

[0009] The above object is further achieved by a mobile terminal for a wireless cellular telecommunication system, with transmitting and receiving means for transmitting information to and receiving information from base stations of said telecommunication system and for receiving mode change information transmitted from a base station by means of a paging message of a paging channel of the wireless telecommunication system for

protecting a predetermined area from disturbing usage of the mobile terminal, and control means for detecting received mode change information and changing an operation mode of the mobile terminal depending on the received mode change information so that said predetermined area is protected.

[0010] The wireless cellular telecommunication system can be any known or future system using paging messages in a broadcast control channel. After switching on a mobile terminal within a cell of a telecommunication system, the mobile terminal registers with the corresponding network through the base station of the cell. After a successful registration the mobile terminal listens to the paging channel of this base station in order to be able to react on incoming phone calls. According to the present invention, the paging messages of the paging channel are used for the transmission of mode change information to protect a predetermined area.

[0011] The predetermined area is thereby the restricted area, in which the particular base station transmits the mode change information. E. g., such a predetermined area could be a hospital or a small area around the boarding gate of an airport or inside a plane.

[0012] The advantage of the described invention is that it does not rely on peoples responsibility to switch off their phones, but that it will perform this automatically. This will provide much higher safety to the areas to be protected. Furthermore the mode change information is not only broadcast to each phone within the cell site, which makes sure that each mobile terminal supporting the mode change functionality will be reached and prevented from disturbing usage; but it also provides the possibility to address individual phones to prevent them from disturbing usage. However, it will still be possible to exempt mobile terminals from groups of people, e.g. security personnel, from mode change, so that these can still utilise the communication tools provided by mobile telephony. A further advantage is that the described invention will only require a very small upgrade to existing systems and therefore additional investment in infrastructure is not necessary. All the described areas can be performed by changes to the software of the infrastructure. The impact on mobile terminals is also kept to a minimum in order to avoid any major impact on the cost of those terminals.

[0013] Advantageously, the mode change information replaces at least partially paging messages in the paging channel. Alternatively, the mode change information is additional information to the paging message in the paging channel. Further, the mode change information can comprise special information for changing a mode only of one or more mobile terminals, which are individually addressed, by said special information. In this case, the special information can be address information individually directed to particular mobile terminals, the mode of which is changed upon receiving the mode change information, whereas other mobile terminals within the predetermined area are not addressed and

have their mode not changed. This solution might be advantageous in predetermined areas, in which the operation mode of only a part of the mobile terminals should be changed and some of the mobile terminals within the predetermined area, e. g. mobile terminals of security personal or the like, should remain usable.

[0014] In case that the mode change information replaces the paging message, the base station according to the present invention can be built very simple and cheap, since it only needs to transmit the mode change information on a particular paging channel and does not need to perform further tasks, such as registration procedures. A mobile terminal switched on within the predetermined area receives the mode change information instead of or in addition to the paging message and changes its operation mode correspondingly.

[0015] The predetermined area to be protected is usually within a cell or adjacent to one or more cells of the telecommunication system. A mobile terminal in one of the neighbouring cells receives information about neighbouring base stations within the system information messages from the current base station. The channels, on which these neighbouring base stations can be found, are monitored by the mobile terminal and when the signal of the current base station becomes weaker and the signal from a neighbouring base station becomes stronger, the mobile terminal will eventually switch to the neighbouring cell. In case that the signal from a neighbouring base station is a mode change information according to the present invention, the mobile terminal will change its mode when the signal carrying the mode change information receives a certain strength, which indicates, that the mobile terminal is entering the predetermined area to be protected.

[0016] Advantageously, the transmitting means of the base station regularly transmits the mode change information. The generating means advantageously generates mode change information for switching off at least the high frequency portion of a mobile terminal receiving said mode change information. The high frequency portion of a mobile terminal, which comprises e. g. upconverting and downconverting means, is the most important part of a mobile terminal to be switched off for avoiding interference with the circuitry of other electronic or electric devices in the predetermined area.

[0017] Alternatively, the generating means generate mode change information for switching a mobile terminal receiving the mode change information into a silent mode, e. g. a ringer off or a vibrating device on mode. In the silent mode, audible or acoustic signals output from the mobile terminal are at least reduced to low volume to avoid a disturbance in the predetermined area. Advantageously, the audible signals are completely suppressed and replaced by visual signals, vibrating signals or other non-audible signals.

[0018] Advantageously, it is possible to define additional information in the change mode information, which excludes groups of mobile terminals from chang-

ing their mode.

[0019] Advantageously, the mobile terminal of the present invention maintains the changed mode as long as the mode change information is received and detected. The mobile terminal could thereby regularly check if the change mode information is still received regularly and changes its mode as soon as the mode change information is not received anymore. The mobile terminal could further comprise a timing means for calculating the time period since the last reception and detection of a mode change information and for comparing the time period with a predetermined time threshold, whereby the mobile terminal is reset to the original mode in case that the time period exceeds the time threshold. Alternatively, the control means maintains the changed mode until a time period received as time information with the mode change information has expired, whereby the mobile terminal is reset to the original mode thereafter. In addition the mode change information may contain a minimum time indication on how long the mode change should apply.

[0020] Advantageously, the transmitting and receiving means of the mobile terminal receives the special information comprised in the mode change information, whereby the special information individually addresses only one or more mobile terminals to change a mode thereof, and said control means of the mobile terminal determines on the basis of the special information if the mobile terminal is addressed and changes its mode in this case.

[0021] Advantageously, the control means, upon detecting mode change information, switches off at least the transmitting part of a high frequency portion of the mobile terminal. The mobile terminal could still receive reset messages, which reset the change mode, through its receiver. However, the receiver still would emit high frequency signals which could disturb other equipment. In case that there is no requirement for reset messages the whole high frequency part of the mobile terminal could be switched off. Further, the entire mobile terminal could be switched off. Alternatively, the control means detecting mode change information switches the mobile terminal into a silent mode, e. g. a ringer off or a vibrating device on mode. As stated above, the silent mode is a mode in which audible or acoustic signals output from the mobile terminal are at least reduced in volume so that disturbance within the predetermined area is avoided. In case that the audible or acoustic signals are suppressed completely, visual signals, vibration signals or the like replace them.

[0022] Advantageously, when the mobile terminal is located in a cell adjacent to the predetermined area, the transmitting and receiving means receives information on the position of the broadcast control channel of the base station according to the present invention for protecting the predetermined area, and then, the control means of the mobile terminal determines the receiving power of the broadcast control channel of the base sta-

tion. This means, that if the mobile terminal is in a normal telecommunication cell adjacent or surrounding the predetermined area, the mobile terminal receives from the current normal base station information on the position of a broadcast control channel, on which the base station indicates the position of the paging channel in the predetermined area for protecting the predetermined area and on which the base station transmits the mode change information. If a user using a mobile terminal is in a telephone conversation and approaches the predetermined area, in which the operation mode of the mobile terminal will be changed, the system will determine from information received from the mobile terminal that the mobile terminal is coming closer to the predetermined area and will therefore issue warning information, either through audible sounds (e.g. in the earpiece) or by signalling information to the mobile terminal, which will then behave according to preset behaviour. When the user receives an alarm signal he will be able to either terminate the conversation or step further away from the predetermined area to be able to continue his conversation.

[0023] In the following description, the present invention is explained in more detail by means of preferred embodiments thereof relating to the enclosed drawings, in which

figure 1 shows a block diagram of a base station according to the present invention and;

figure 2 shows a block diagram of a reduced base station according to the present invention and;

figure 3 shows a block diagram of a mobile terminal according to the present invention and;

figure 4 shows a principle outline of standard cell-sites adjacent to areas to be protected according to the present invention and;

figure 5 shows the principle system architecture of a cellular network according to the present invention.

[0024] The base station 1 shown in figure 1 is a base station for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system. The base station 1 comprises generating means 2 for generating mode change information for changing an operation mode of the mobile terminals within the predetermined area to protect the predetermined area. The base station 1 further comprises transmitting means 3 for transmitting mode change information generated in the generating means 2 within the predetermined area using paging messages of a paging channel of the wireless telecommunication system. The mode change information is transmitted from the transmitting means 3 by means of an antenna 5.

[0025] The base station 1 can be a normal base station for transmitting and receiving signals in the wireless cellular telecommunication system or a special base station 1' as outlined in figure 2 only transmitting said mode change information for protecting the predetermined area. In the first case, the base station 1 further comprises receiving means 4 as shown in figure 1. In the second case, the base station 1' essentially comprises only a generating means 2' and a transmitting means 3', so that a very simple and cost-effective solution is achieved. The base station 1 comprising only the transmitting means 3' and the generating means 2' only serves for transmitting the mode change information within the predetermined area without having further capabilities. The transmitting means 3' and the generating means 2' have the same functions as the transmitting means 3 and the generating means 2. For ease of operation an external or internal control terminal or PC 19 could be connected.

[0026] Of course, the base station 1 in figure 1 comprises further elements which are necessary to operate the base station 1 in the respective telecommunication system, e. g. a control means 6 and so on. The base station 1 operates and transmits the mode change information on the basis of the wireless cellular telecommunication system, i. e. the GSM-system or the like. This has the advantage that mobile terminals entering the predetermined area can be addressed on the basis of the wireless cellular telecommunication system to change an operation mode thereof to protect a predetermined area without requiring a different receiving section for the mode change information transmitted from the base station 1. This has the additional advantage that the mobile terminals, as e. g. the mobile terminal 7 shown in figure 3, can be common mobile terminals for the wireless telecommunication system, which only need to be adapted to receive and process the mode change information. Thus, the configuration of normal mobile terminals for the wireless telecommunication system does not need to be changed essentially.

[0027] In figure 3, a bloc diagram of a mobile terminal 7 according to the present invention is shown. The mobile terminal 7 comprises transmitting and receiving means 8 for transmitting information to and receiving information from base stations of the telecommunication system. The transmitting and receiving means 8 further receive mode change information transmitted from a base station by means of paging messages of a paging channel of the wireless telecommunication system for protecting a predetermined area from disturbing usage of the mobile terminal. E. g., the base station transmitting the mode change information can be the base station 1 of figure 1 or the reduced base station 1' of figure 2. The transmitting and receiving means 8 comprises a transmitting unit 9 and a receiving unit 10. The receiving unit 10 of the transmitting and receiving means 8 receives signals by means of an antenna 18. The received

signals are then processed in the mobile terminal 7 under control of a control means 11. E. g., the received signals are decoded in a decoding means 15, whereby further processing steps depending on the structure of the signals might be taken. At the end of the processing, the signals are either transformed into audible signals and output from a loudspeaker 13 in case they are voice signals, or answered by the mobile terminal in case they are signalling information, or passed on to the data part or a data device in case they are data signals.

[0028] The mobile terminal 7 further comprises a microphone 12 for receiving and detecting acoustic signals. The signals input in the microphone 12 are further processed under the control of the control means 11, e. g. coded in a coding means 14 and so on depending on the structure of the signals in the telecommunication system, and then transmitted by the transmitting unit 9 through the antenna 18. The mobile terminal 7 comprises further elements for processing received signals and signals to be transmitted besides the decoding means 15 and the coding means 14 as shown in figure 3. The additional elements depend on the structure of the signals in the wireless telecommunication system, so that a large variety of further processing units can be implemented.

[0029] The mobile terminal 7 further comprises a generating means 16 connected between the control means 11 and the transmitting unit 9 and a timing means 17 connected with the control means 11.

[0030] Figure 4 shows the topography of e.g. an airport terminal, where areas A and B are the coverage areas of a cell site, covering the waiting lounge X. Areas C1, C2 and C3 indicate the coverage area of cell sites covering a predetermined area, e.g. the gangway towards an airplane, Y, Z1 and Z2. As long as a user is making phone calls or is walking in areas "A" and "B" his phone will work normally and nothing will happen. Once he is approaching the area "C" the network may issue warning indications to the phone while it is in communication, warning the user that he is coming closer to a predetermined area. Once the user enters the area "C", "C2" or "C3" the telephone will receive the mode change information and change its mode accordingly. This functionality not necessarily requires separate cell sites, this could also be handled in area "C1" alone.

[0031] The base station 1 being located in an area which has to be protected from a disturbing usage of mobile terminals, regularly broadcasts mode change information which is received by mobile terminals, as e. g. a mobile terminal 7, entering the predetermined area to change an operation mode thereof so that the area is protected. Thereby, the mode change information is broadcasted from the base station 1 on the basis of paging messages in a paging channel of the wireless telecommunication system.

[0032] Figure 5 shows the basic structure of a cellular system, which comprises at least two base stations 1, covering the areas A and B, a base station controller 20,

a switch 21 with a gateway to a public telephone network 22, a register 23 which keeps information on the terminals of this cellular network and possibly of visiting mobile terminals and the mobile terminals 7 themselves. The base stations are connected with the base station controller via a communication and signalling link, the base station controller and the switch is connected via a communication and signalling link, the register and the switch are connected by a communication and signalling link, as well as the switch and the public telephone network. The mobile terminals 7 and the base stations 1 communicate by means of radio transmissions.

[0033] Usually, when a mobile terminal is switched on the first time, it reads system information from a broadcast control channel. Once it has the knowledge about timing, channel structure, location including the network identification of the particular base station of the respective cell of the telecommunication system, the mobile terminal will try to register itself with the network through this base station. This means, that the mobile terminal makes itself known to the network, so that the network will be able to page the mobile terminal later on. After a successful registration a mobile terminal will listen regularly to the paging channel of the respective base station in order to be able to react on incoming phone calls. Furtheron, the mobile terminal monitors base stations in neighbouring cells, the channels of which are listed in the system information of the current cell. A paging area can comprise several cells, in which a particular mobile terminal is paged. When a mobile terminal is moving around in the network, the signal of the base station of the current cell will become weaker and a signal from a neighbouring cell will become stronger. Eventually, the mobile terminal switches to the base station of the neighbouring cell. This is true, when the mobile terminal is in the idle mode, when the mobile terminal is in the talk mode, a cell change, i. e. a hand-over, is initiated by the network. In other cellular systems, e.g. CDMA One, the mobile station itself would decide on its own whether to perform a handover or not. Once the mobile terminal has switched to the base station of the neighbouring cell, it will again read all necessary information from the system information message broadcast on the broadcast control channel from the base station of the new cell. If this new cell belongs to the same paging area as the previous cell, the mobile terminal will not perform a registration (location update). In case that the base terminal belongs to a new paging area, the mobile terminal will perform a registration (location update).

[0034] Thus, two scenarios are possible. The first scenario is that the mobile terminal 7 located within a predetermined area to be protected is switched on being within the predetermined area. The predetermined area, which is an area to be protected from disturbing usage of mobile terminals, is usually located within a cell of the wireless telecommunication or on an intersection of two or more adjacent cells of the wireless telecommunication system. Thus, the mobile terminal within the prede-

termined area will register to a base station of one of the cells of the wireless telecommunication system. The mobile terminal registered to one of the base stations of a normal cell will then regularly monitor the paging channels in order to be able to receive paging messages. If a mobile terminal being within the predetermined area receives the mode change information on the paging channel from the base station 1, the mobile terminal will change its operation mode correspondingly. A similar procedure takes place in case that the mobile terminal is within an adjacent cell of the telecommunication system. The detection of the mode change takes place in the control means 11 of the mobile terminal 7.

[0035] The mode change information generated in the generating means 2 of the base station 1 can be additional information to the paging messages or can replace at least partially the paging messages in the paging channel. Normal paging messages transmitted from a normal base station of a normal cell in the telecommunication system either contain dummy bursts or paging information addressing one or more particular mobile terminals to which a call is directed. Thus, the mode change information transmitted by the base station 1 for protecting the predetermined area replaces e. g. a dummy burst of a paging message or a particular paging information in the paging channel or is additional information to the different types of paging messages.

[0036] The mode change information generated in the generating means 2 of the base station 1 can additionally comprise special information for changing the operation mode only of one or more mobile terminals which are individually addressed by said special information. Thus, the special information can contain address information addressing particularly specified mobile terminals. A mobile terminal receiving the mode change information, as e. g. the mobile terminal 7, receives the special information comprised in the mode change information with the transmitting and receiving means 8, whereby the control means 11 determines on the basis of the special information if the mobile terminal 7 is addressed and changes the operation mode of the mobile terminal 7 if this is the case.

[0037] As stated above, a simple and cost-effective version of the base station 1 essentially comprises the generating means 2 and the transmitting means 3 so that only mode change information is generated and transmitted by the base station 1. In this case, the system information messages do not need to contain additional information and it is sufficient only to transmit the mode change information instead of the paging message in the paging channel. The mobile terminal 7 will then receive only the mode change information and change its mode correspondingly. In a more developed version of the base station 1 the mode change information replace only a part of the paging message in the paging channel, so that further information like the reason for the mode change, the level of the mode change or the like can be transmitted to the mobile terminal 7.

Particularly, the mobile terminal 7 does not need to register with the base station 1 for protecting the predetermined area. It is sufficient, when the mobile terminal 7 receives the mode change information from the base station 1 to change its mode to protect the area. The base station 1 of the predetermined area to be protected is thereby treated as a normal neighbouring base station of an adjacent cell. In case that the mobile terminal 7 is registered to a normal base station in a cell of the telecommunication system, this normal base station comprises in its system information messages information about the channels of the neighbouring base stations. If one of the neighbouring base stations is the base station 1 for protecting the predetermined area, the mobile terminal 7 will regularly monitor the broadcast control channel of the base station 1 as it does with the other adjacent base stations. As soon as the mobile terminal switches to the base station 1 for protecting the predetermined area, the mobile terminal will read the system information and after that listen to the paging channel, carrying the change mode information which will force the mobile terminal to change a mode thereof since the predetermined area is reached.

[0038] In any case, the control means 11 of the mobile terminal 7 can cause the loudspeaker 13 to output an alarm signal to warn a user that he is approaching or within the predetermined area to be protected and that the operation mode of the mobile terminal 7 will be changed soon to protect the area. Thus, the user can decide to get away from the predetermined area or, in case that a call is in progress, he can terminate the conversation quickly.

[0039] Upon receiving a mode change information by the transmitting and receiving means 8, the control means 11 of the mobile terminal 7 detects the mode change information and changes the mode of the mobile terminal 7 depending on the received mode change information so that the predetermined area is protected. The control means 11 can thereby maintain the changed mode as long as mode change information is regularly received and detected. As soon as mode change information is no longer received, the mobile terminal 7 is reset to its original mode before the mode change. The timing means 17 of the mobile terminal 7 may calculate the time period since the last reception and detection of the mode change information and for comparing the time period with a predetermined time threshold, whereby the mobile terminal 7 is reset to the original mode in case that the time period exceeds the time threshold. If a time indication is present in the mode change information, the mobile terminal must not attempt a reset before the indicated time.

[0040] Alternatively, the control means 11 maintain the changed mode until the time period received as time information together with the mode change information has expired, whereby the mobile terminal 7 is reset to the original mode thereafter. In this case, the generating means 2 of the base station 1 needs to generate addi-

tional time information to the mode change information to indicate how long the changed mode in the mobile terminal 7 should be maintained. Another possibility is to store the time information in the mobile terminal 7 so that the time period during which the changed mode has to be maintained is provided by the mobile terminal 7 itself.

[0041] If e. g. the predetermined area to be protected is a hospital, where it has to be assured that mobile terminals are not used, the mobile terminals advantageously maintain their changed mode as long as the mode change information is received. In this case, one or more base stations 1 are located in the hospital and regularly broadcast the mode change information. A further possibility might be to change the mode of mobile terminals upon receiving a mode change information, e. g. at a boarding gate of an airport, to maintain the changed mode during the flight and to reset the mode of the mobile terminals upon receiving a second mode change information at the exit gate of the airport on the arrival.

[0042] Depending on the received mode change information, the control means 11 of the mobile terminal 7 changes the operation mode thereof. If areas like a hospital or airplane are to be protected, the control means 11 switches off at least a high frequency portion of the mobile terminal 7. The high frequency portion of the mobile terminal is the part causing interference with other electronic or electric devices and thus the operation of the high frequency part should be suppressed. In case of the mobile terminal 7 shown in figure 3, the control means 11 could switch off at least the transmitting unit 9 of the transmitting and receiving means 8 upon receiving a mode change information. The mobile terminal 7 is then still able to receive signals by means of the receiving unit 10, e. g. to receive information to reset the mobile terminal 7 to its original mode. Alternatively, the control means 11 could switch off the entire transmitting and receiving means 8 so that neither the transmission nor the reception of signals is possible any longer. In both cases, however, the base band functions could still be available, so that a user still can edit information, input information to the internal telephone book, store messages to be transmitted later on and the like.

[0043] In other areas, e. g. restaurants, operas, theatres or the like, it is sufficient to change the mode of the mobile terminal 7 into a silent mode, in which other people in the same area are not annoyed by audible or acoustic signals output from the mobile terminal 7. Thereby it might be sufficient if the control means 11 simply reduces the volume of the acoustic signals to be output by the loudspeaker 13. Further, the volume of signals to be output by the loudspeaker 13 could be completely suppressed. Additionally to the reduced volume signals or replacing the suppressed audible signals, the control means 11 might cause the output of the visual signals on a display of the mobile terminal 7, the activating of a vibration device of the mobile terminal 7 or

the like to indicate incoming phone calls to a user.

#### Claims

1. Base station (1, 1') for protecting a predetermined area from disturbing usage of mobile terminals of a wireless telecommunication system, with
  - generating means (2, 2') for generating mode change information for changing an operation mode of said mobile terminals to protect said predetermined area ,
  - transmitting means (3, 3') for transmitting said generated mode change information within said predetermined area by means of a paging message of a paging channel of said wireless telecommunication system.
2. Base station (1, 1') according to claim 1, **characterized in**, that said mode change information replaces at least partially said paging messages in said paging channel.
3. Base station (1, 1') according to claim 1, **characterized in**, that said mode change information is additional information to said paging messages in said paging channel.
4. Base station (1, 1') according to claim 1, 2 or 3 **characterized in**, that said mode change information comprise special information for changing a mode only of one or more mobile terminals which are individually addressed by said special information.
5. Base station (1, 1') according to one of the claims 1 to 4, **characterized in**, that said transmitting means (3, 3') regularly transmits said mode change information.
6. Base station (1, 1') according to one of the claims 1 to 5, **characterized in**, that said generating means (2) generates mode change information for switching off at least a high frequency portion of a mobile terminal receiving said mode change information.
7. Base station according to one of the claims 1 to 5, **characterized in**, that said generating means (2, 2') generates mode change information for switching a mobile terminal receiving said mode change information into a silent mode, e.g. ringer off, vibrating device on.
8. Base station (1, 1') according to one of the claims 1 to 7, **characterized in**, that said generating means (2, 2') generates time information additionally to said mode change information for indicating a time period during which the changed mode of a mobile terminal is to be maintained.
9. Base station (1, 1') according to one of the claims 1 to 8, **characterized in**, that said generating means (2, 2') generates information on the reason of the mode change additionally to said mode change information.
10. Base station (1, 1') according to one of the claims 1 to 9, **characterized in**, that said generating means (2, 2') generates information on groups of mobile terminals to be exempted from the mode change.
11. Method for protecting a predetermined area from disturbing usage of mobile terminals of a wireless cellular telecommunication system, with the steps of generating mode change information for changing an operation mode of said mobile terminals to protect said predetermined area from disturbing usage of mobile terminals, transmitting said generated mode change information within said predetermined area by means of paging messages of a paging channel of said wireless telecommunication system.
12. Method according to claim 9 to 11, **characterized in**, that said mode change information replace at least partially said paging messages in said paging channel.
13. Method according to claim 11, **characterized in**, that said mode change information are additional information to said paging messages in said paging channel.
14. Method according to one of the claims 11 to 13, **characterized in**, that said mode change information comprise special information for changing a mode only of one or more mobile terminals which is or are individually addressed by said special information.
15. Method according to one of the claims 11 to 14, **characterized in**, that said mode change information is regularly transmitted.



16. Method according to one of the claims 11 to 15,  
**characterized in,**  
that said mode change information switches off at  
least a high frequency portion of a mobile terminal  
receiving said mode change information. 5
17. Method according to one of the claims 11 to 15,  
**characterized in,**  
that said mode change information switches a  
mobile terminal receiving said mode change infor- 10  
mation into a silent mode, e.g. ringer off, vibrating  
device on.
18. Mobile terminal (7) for a wireless cellular telecom- 15  
munication system, with
- transmitting and receiving means (8) for trans-  
mitting information to and receiving information  
from base stations of said telecommunication  
system and for receiving mode change infor- 20  
mation transmit from a base station by means  
of paging messages of a paging channel of said  
wireless telecommunication system for protect-  
ing a predetermined area from disturbing usage  
of the mobile terminal, 25  
control means (11) for detecting received mode  
change information and changing a mode of the  
mobile terminal depending on the received  
mode change information so that said prede- 30  
termined area is protected.
19. Mobile terminal (7) according to claim 18,  
**characterized in,**  
that said control means (11) maintain said changed 35  
mode as long as the mode change information is  
received and detected.
20. Mobile terminal (7) according to claim 18 or 19,  
**characterized in,**  
that a timing means (17) for calculating the time pe- 40  
riod since the last reception and detection of said  
mode change information and for comparing said  
time period with a predetermined time threshold is  
provided, whereby the mobile terminal is reset to 45  
the original mode in case that the time period ex-  
ceeds said time threshold.
21. Mobile terminal (7) according to claim 18 or 19,  
**characterized in,**  
that said control means (11) maintain said changed 50  
mode until a time period received as time infor-  
mation with said mode change information has ex-  
pired, whereby the mobile terminal is reset to the  
original mode thereafter. 55
22. Mobile terminal (7) according to one of the claims  
18 to 21,  
**characterized in,**
- that said transmitting and receiving means (8) re-  
ceives said special information comprised in said  
mode change information, whereby said special in-  
formation individually addresses only one or more  
mobile terminals to change a mode thereof, and  
said control means (11) determines on the basis of  
said special information if the mobile terminal is ad-  
dressed and changes its mode in this case.
23. Mobile terminal (7) according to one of the claims  
18 to 22,  
**characterized in,**  
that said control means (11) detecting said mode  
change information switches off at least a high fre-  
quency portion of the mobile terminal.
24. Mobile terminal (7) according to one of the claims  
18 to 22,  
**characterized in,**  
that said control means (11) detecting said mode  
change information switches the mobile terminal in-  
to a silent mode, e.g. ringer off, vibrating device on.
25. Mobile terminal (7) according to one of the claims  
18 to 24,  
**characterized in,**  
that in case of being located in an cell adjacent to  
said predetermined area said transmitting and re-  
ceiving means (8) receives information on the posi-  
tion of the paging channel of the base station for  
protecting said predetermined area, said control  
means (11) determines the receiving power of the  
paging channel of the base station and outputs a  
warning signal to a user upon approaching the pre-  
determined area to warn the user that a mode of the  
mobile terminal will be changed soon.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 10 7648

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 97 49255 A (NOKIA MOBILE PHONES LTD ;IDMAN JOHAN (FI); KANGAS SAKARI (FI); KUR) 24 December 1997 (1997-12-24)  * page 5, line 21 - page 7, line 28 *	1,4,6,7, 11,14, 16-18, 22-24	H04Q7/38
A	US 5 862 470 A (DAMGHANI YAMIN) 19 January 1999 (1999-01-19) * column 3, line 11 - column 10, line 48 *	1,8,11, 18-21	
A	EP 0 873 033 A (NIPPON ELECTRIC CO) 21 October 1998 (1998-10-21)  * column 9, line 27 - column 14, line 3 *	1,4,6,7, 11,14, 16-18, 22-25	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04Q
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>1 November 1999</b>	Examiner <b>Weinmiller, J</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons  & : member of the same patent family, corresponding document	

EPO FORM 1503 (01.02.1994)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 10 7648

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-11-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9749255	A	24-12-1997	FI	962518 A	18-12-1997
			AU	2901397 A	07-01-1998
US 5862470	A	19-01-1999	NONE		
EP 0873033	A	21-10-1998	JP	10290481 A	27-10-1998

EPO FORM P4488

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82